



FlexScan Office Monitors

The most advanced technology, the most innovative features,
and the best picture quality. Let us introduce: our office monitors.

Optimal ergonomics

- ◆ Height adjustable, rotatable and tiltable
- ◆ Auto EcoView: automatic brightness adjustment
- ◆ Flicker-free images thanks to hybrid brightness control
- ◆ Matte anti-glare coating
- ◆ Narrow housing bezel
- ◆ Ideal for multi-monitor solutions

Environmentally conscious and sustainable

- ◆ Environmentally and climate-friendly production with measures to reduce waste, wastewater and emissions
- ◆ Careful use of resources and energy
- ◆ Sustainable packaging materials
- ◆ High recyclate content in housing plastics
- ◆ Production without child or forced labor
- ◆ No use of minerals from critical sources

Cost-efficient and economical

- ◆ Equipped with energy-saving features such as Auto EcoView, real power switch
- ◆ Compliance with international guidelines for energy savings and ergonomics according to Energy Star, EPEAT, TCO and TÜV
- ◆ Lowest failure rates and highest investment security (TCO)
- ◆ 5-year warranty incl. on-site replacement service



Best connectivity

- ◆ Graphics and audio signal via USB-C, DisplayPort or HDMI
- ◆ Charging power for notebook via USB-C power delivery
- ◆ LAN port and KVM switch for maximum functionality
- ◆ Peripheral connection via USB ports
- ◆ Fewer cables due to USB-C daisy chaining

Working with the Best



FlexScan monitors at a glance



	EV4340X	EV3895	EV3450XC	EV3240X	EV2740X	EV2795	EV2495	EV2490	EV2781	EV2485	EV2480	EV2760	EV2456	EV2430	EV2460	EV2360
Screen size	42.5" Aspect ratio 16:9	37.5" Aspect ratio 24:10 Curved Ultrawide	34.1" Aspect ratio 21:9 Curved Ultrawide	31.5" Aspect ratio 16:9	27" Aspect ratio 16:9	27" Aspect ratio 16:9	24.1" Aspect ratio 16:10	23.8" Aspect ratio 16:9	27" Aspect ratio 16:9	24.1" Aspect ratio 16:10	23.8" Aspect ratio 16:9	27" Aspect ratio 16:9	24.1" Aspect ratio 16:10	24.1" Aspect ratio 16:10	23.8" Aspect ratio 16:9	22.5" Aspect ratio 16:10
Resolution	3,840×2,160 (4K UHD)	3,840×1,600	3,440×1,440	3,840×2,160 (4K UHD)	3,840×2,160 (4K UHD)	2,560×1,440	1,920×1,200	1,920×1,080	2,560×1,440	1,920×1,200	1,920×1,080	2,560×1,440	1,920×1,200	1,920×1,200	1,920×1,080	1,920×1,200
Max. Brightness	350 cd/m ²	300 cd/m ²	300 cd/m ²	350 cd/m ²	350 cd/m ²	350 cd/m ²	350 cd/m ²	250 cd/m ²	350 cd/m ²	350 cd/m ²	250 cd/m ²	350 cd/m ²	350 cd/m ²	300 cd/m ²	250 cd/m ²	250 cd/m ²
Signal inputs	1× USB-C 1× DisplayPort 2× HDMI	1× USB-C 1× DisplayPort 2× HDMI	1× USB-C 1× DisplayPort 2× HDMI	1× USB-C 1× DisplayPort 2× HDMI	1× USB-C 1× DisplayPort 2× HDMI	1× USB-C 1× DisplayPort 1× HDMI	1× USB-C 1× DisplayPort 1× HDMI	1× USB-C 1× DisplayPort 1× HDMI	1× USB-C 1× DisplayPort 1× HDMI	1× USB-C 1× DisplayPort 1× HDMI	1× USB-C 1× DisplayPort 1× HDMI	2× DisplayPort 1× HDMI 1× DVI-D	1× DisplayPort 1× HDMI 1× DVI-D 1× D-sub	1× DisplayPort 1× DVI-D 1× D-sub	1× DisplayPort 1× HDMI 1× DVI-D 1× D-sub	1× DisplayPort 1× HDMI 1× D-sub
USB ports	Upstream: 1× USB-C 1× USB-B Downstream: 1× USB-C 2× USB-A	Upstream: 1× USB-C 2× USB-B Downstream: 4× USB-A	Upstream: 1× USB-C 1× USB-B Downstream: 1× USB-C 2× USB-A	Upstream: 1× USB-C 1× USB-B Downstream: 1× USB-C 3× USB-A	Upstream: 1× USB-C 1× USB-B Downstream: 1× USB-C 3× USB-A	Upstream: 1× USB-C 1× USB-B Downstream: 1× USB-C 3× USB-A	Upstream: 1× USB-C 1× USB-B Downstream: 1× USB-C 3× USB-A	Upstream: 1× USB-C 1× USB-B Downstream: 1× USB-C 3× USB-A	Upstream: 1× USB-C Downstream: 4× USB-A	Upstream: 1× USB-C Downstream: 4× USB-A	Upstream: 1× USB-C Downstream: 4× USB-A	Upstream: 1× USB-B Downstream: 4× USB-A	Upstream: 1× USB-B Downstream: 2× USB-A	Upstream: 1× USB-B Downstream: 2× USB-A	Upstream: 1× USB-B Downstream: 4× USB-A	Upstream: 1× USB-B Downstream: 2× USB-A
Webcam and microphone	-	-	◆	-	-	-	-	-	-	-	-	-	-	-	-	-
USB-C Power Delivery	94 W	85 W	94 W	94 W	94 W	70 W	70 W	70 W	70 W	70 W	70 W	-	-	-	-	-
USB-C Daisy Chaining	-	-	-	-	-	◆	◆	◆	-	-	-	-	-	-	-	-
LAN port	◆	◆	◆	◆	◆	◆	◆	◆	-	-	-	-	-	-	-	-
KVM Switch	◆	◆	◆	◆	◆	◆	◆	◆	-	-	-	-	-	-	-	-
Energy label	E	E	F	D	D	D	C	C	D	C	C	E	D	E	B	C
Stand	Two rigid feet Height: 60mm	Tilt range: 35° to the back 5° to the front Rotation: 70° Height adjustment: 192.7mm	Tilt range: 35° to the back 5° to the front Rotation: 90° Height adjustment: 195mm	Tilt range: 35° to the back 5° to the front Rotation: 90° Height adjustment: 195mm	Tilt range: 35° to the back 5° to the front Rotation: 90° Height adjustment: 195mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 176.6mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 182.2mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 191.2mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 176.6mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 182.2mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 191.2mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 169mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 158.6mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 131mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 140mm	Tilt range: 35° to the back 5° to the front Rotation: 344° Height adjustment: 140mm
Five-Year Warranty	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries.
All other product names are trademarks or registered trademarks of their respective owners.

To assist you, we offer free loan units for testing and technical support in both pre-sales and after-sales.
Find your local sales partners or EIZO contact persons: [eizo.eu/contact](https://www.eizo.eu/contact)

Copyright © 2024 EIZO Europe GmbH - Vestiging Nederland, Dr. Holtroplaan 34-36, 5652 XR Eindhoven.
All rights, errors and modifications are subject to change. Last updated: Juli 2024

